

SUN ELECTRIC CORPORATION

Model: SUN MRC-300-3

Page:

1 of 3

# Field Installation Instructions

INSTALLATION MUST BE PERFORMED BY QUALIFIED SUN SERVICE PERSONNEL ONLY

INSTALLATION OVERVIEW:

The Installation Procedures listed are for the SUN MRC-300-3 (220V). The unit is shipped as a fully assembled unit, with the exception of the items as listed in the Parts List.

PARTS LIST: -

DESCRIPTION Literature Kit, MRC-300	<b>PART NUMBER</b> 0119-0319-01	QUANTITY 1
GM Adapter	0647-0196-01	1
GM/Ford Adapter, Quick-Disconnect	0647-0197-01	1
90 Degree Adapter	0647-0198-01	1
Large CM Adapter, Quick-Disconnect	0647-0199-01	1
Ford Adapter	0647-0200-01	1
Tool Pouch	0671-1012-01	1
Desiccant Bag	0671-1018-01	10
Installation Instructions	0692-1964-01	1
cap Plug	1374-0111-01	6
Yellow Charge Hose Assembly	3988-0232-01	1
Red Hose Assembly, 96"	3988-0233-01	1
Blue Hose <b>Assembly</b> , 96"	3988-0234-01	1
Red Hose Assembly, with Hand Valve	3988-0235-01	1
Blue Hose <b>Assembly</b> with <b>Hand</b> Valve	3988-0236-01	1
Tank <b>Power</b> Cable Assembly	6004-0668-01	1
Gauge Set Assembly w/o Hoses	7009-2082-02	1
Reclaim Tank Assembly	7009-2083-01	1

REQUIRED TOOLS:

Complete Sun Issued Tool Kit Safety Goggles (0001-5005)

## USE STANDARD REFRIGERANT HANDLING SAFETY PROCEDURES WHEN PERFORMING THIS PROCEDURE

#### GADGE SET ASSEMBLY

- 1. Open the container and remove the unit and allaccessories from the shipping container.
- 2. Inventory all items using the parts list and inspect for damage.
- 3. Attach the YELLOW Charge Hose Assembly (3988-0232-01) to the middle connector on the Gauge Set Assembly (7009-2082-02).
- 4. Attach the opposite end of the YEILOW Charge Hose Assembly to the Intake Port on the back of the unit.
- 5. Attach the BLUE Hose Assembly (3988-0234-01) to the low pressure side of the Gauge Set Assembly (BLUE handle side).
- 6. Attach the RED Hose Assembly (3988-0233-01) to the high pressure side of the Gauge Set Assembly (RED handle side).
- 7. Attach the BLUE Hose Assembly with Hand Valve (3988-0236-01) to the BLUE Hose Assembly.
- 8. Attach the RED Hose Assembly with Hand Valve (3988-0235-01) to the RED Hose Assembly.
- NOTE: The hoses that are supplied with the Hand Valves have an angled fitting with a Schrader Valve depressor on one end, and a straight fitting with no depressor on the other end. The straight fittings on the hoses are attached to the Hand Valve and the fitting with the depressor will attach to the Vehicle that is to be serviced.

#### RECLAIM TANK

- 9. Remove the Reclaim Tank Assembly (7009-2083-01) from the packing container.
- 10. Open the LIQUID Valve on the Tank Assembly to relieve any pressure that may be left in the tank.
- 11. Secure the Reclaim Tank Assembly on the **bottom** shelf by using the velcro **strap.**
- 1.2. Connect the BLUE Hose Assembly that is attached to the Gauge Set Assembly to the port marked LIOUID.
- 13. Ensure that the VAPOR valve IS closed.
- 14. Ensure that the LIQUID Valve is open.
- 15. Open the Hand Valve on the BLUE Hose Assembly.

### Page 3 of 3

- 16. Open the BLUE Valve on the Gauge Set Assembly.
- 17. close the RED valve on the Gauge set Assembly.
- 18. Ensure that the RED Hand Valve is closed.

NOTE: Ensure all unit switches are in the OFF position.

- 19. Plug in the unit to a grounded AC receptacle.
- 20. Turn the Power Switch to "ON".
- 21. Place the RECLAIM/VACUUM switch to the "VACUUM" position.
- 22. Allow the unit to run until the low pressure gauge reads a vacuum of 24" to 29" for fifteen (15) minutes.
- 23. Turn all switches to the "OFF" position.
- 24. Close hand valve on the end of the BLUE Hose, then close the LIQUID valve on the Reclaim Tank.
- 25. Disconnect the BLUE Hose from the tank.

FINAL ASSEMBLY

- 26. Attach the BLUE Hose that extends through the left leg of the unit to the LIQUID Port on the Reclaim Tank Assembly.
- 27. Attach the RED Hose from the Left Leg Vapor Port to the VAPOR Port on the Reclaim Tank Assembly.
- 28. Open both Tank valves.
- 29. Place Tool Pouch (0671-1012-01) over the handle and secure with velcro.
- 30. Store all accessories in the tool pouch.
- 31. Complete the questionnaire (0692-1834-01).

\* INSTALLATION COMPLETE \*

#### CHECKOUT PROCEDURE: -

Refer to **Operator's** Manual in **the Literature** Kit (0119-0319-01) for Checkout **and Customer** Training procedures.